

I CLAIM:

1. A storage system, comprising:
 - a host interface for receiving input/output (“I/O”) transactions from a host device, said I/O transactions complying with a first interface protocol;
 - 5 a storage device interface for transmitting I/O transactions to a plurality of storage devices according to a second interface protocol; and
 - an interface adapter coupled to the host interface and the storage device interface, wherein said interface adapter is configured to receive I/O transactions from the host interface, to convert the I/O transactions from the first interface protocol to the second interface protocol, and to transmit the converted I/O transactions to the storage device interface, and said interface adapter is further configured to receive I/O transactions from the storage device interface, to convert the I/O transactions from the storage device interface from the second interface protocol to the first interface protocol, and to transmit the converted I/O transactions to the host interface.
- 10 2. The storage system of Claim 1, wherein:
 - the second interface protocol is an IDE/ATA interface protocol.
- 15 3. The storage system of Claim 1, wherein:
 - the first interface protocol is a SCSI interface protocol.
- 20 4. The storage system of Claim 1, wherein:
 - the first interface protocol is a Fibre Channel interface protocol.
- 25 5. The storage system of Claim 1, wherein:
 - said interface adapter is configured to receive a first plurality of frames corresponding to an I/O transaction generated by the host device, wherein said interface adapter is configured to convert said first plurality of frames into a plurality of register inputs and a command input corresponding to said I/O transaction, wherein said interface adapter is configured to cause said plurality of register inputs to be
- 30

loaded into a plurality of registers on one of said plurality of storage devices, and wherein said interface adapter is configured to cause said command input to be loaded into a command register on said one of said plurality of storage devices.

6. The storage system of claim 5, wherein said first plurality of frames arrive at said interface adapter in a serial format, and wherein said interface adapter is configured to deserialize said first plurality of frames.

7. The storage system of claim 5, wherein:

said interface adapter includes a first receive buffer and a first transmit buffer coupled to the host interface, and said interface adapter further includes a second receive buffer and a second transmit buffer coupled to the storage device interface, wherein said first plurality of frames is received in said first receive buffer, and wherein said plurality of register inputs is received in said second transmit buffer prior to being loaded into said plurality of registers.

8. The storage system of claim 5, wherein:

said interface adapter is configured to receive a plurality of register outputs from the storage device interface, convert said plurality of register outputs to a second plurality of frames, and convey said second plurality of frames to said host interface.

9. The storage system of Claim 1, wherein:

said interface adapter includes a state machine configured to receive a plurality of frames corresponding to an I/O transaction from said host interface, wherein said state machine is configured to convert said plurality of frames into a plurality of register inputs and a command input corresponding to said I/O transaction, wherein said state machine is configured to cause said plurality of register inputs to be loaded into a plurality of registers on one of the plurality of storage devices, and wherein said state machine is configured to cause said command input to be loaded into a command register on said one of the plurality of storage devices.

10. The storage system of Claim 9, wherein said plurality of frames arrive at said state machine in a serial format, and wherein said state machine is configured to deserialize said plurality of frames.

5

11. The storage system of Claim 9, further comprising:
a first receive buffer coupled to said host interface;
a first transmit buffer coupled to said host interface;
a second receive buffer coupled to said storage device interface; and
10 a second transmit buffer coupled to said storage device interface;
wherein said plurality of frames is received in said first receive buffer, and said plurality of register inputs is received in said second transmit buffer prior to being loaded into said plurality of registers.

5

12. A method of operating a storage system, comprising:
receiving I/O transactions from a host device, said I/O transactions complying with a first interface protocol, said first interface protocol being a SCSI interface protocol or a Fibre Channel interface protocol;
20 converting the I/O transactions from the first interface protocol to a second interface protocol; and
transmitting the I/O transactions to a storage device having an interface complying with the second interface protocol, said second interface protocol being an IDE/ATA interface protocol.

25

13. The method of Claim 12, wherein:
said receiving I/O transactions from the host device comprises receiving a first plurality of frames corresponding to an I/O transaction generated by the host device;
said converting the I/O transactions from the first interface protocol to the second
30 interface protocol comprises converting said first plurality of frames into a

plurality of register inputs and a command input corresponding to said I/O transaction; and

said transmitting the I/O transactions to the storage device comprises:

loading said plurality of register inputs into a plurality of registers on the storage device; and

loading said command input into a command register on one of said plurality of storage devices.

14. The method of claim 13, wherein:

said receiving the first plurality of frames comprises receiving the first plurality of frames in a serial format, and

said converting the I/O transactions from the first interface protocol to the second interface protocol comprises deserializing said first plurality of frames.

15. The method of claim 13, further comprising:

in response to the command input being loaded into the command register of the storage device, executing an operation on the storage device corresponding to said I/O transaction.

16. A storage system, comprising:

a host interface for receiving input/output ("I/O") transactions from a host device, said I/O transactions complying with a first interface protocol;

a plurality of storage devices configured to receive I/O transactions according to a second interface protocol; and

an interface adapter coupled to the host interface and the plurality of storage devices, wherein said interface adapter is configured to receive I/O transactions from the host interface, to convert the I/O transactions from the first interface protocol to the second interface protocol, and to transmit the converted I/O transactions to one of the plurality of storage devices, and said interface adapter is further configured to receive I/O transactions from the plurality of storage devices, to

convert the I/O transactions from the plurality of storage devices from the second interface protocol to the first interface protocol, and to transmit the converted I/O transactions to the host interface.

- 5 17. The storage system of Claim 16, wherein:
 the second interface protocol is an IDE/ATA interface protocol.
18. The storage system of Claim 16, wherein:
 the first interface protocol is a SCSI interface protocol.
- 10 19. The storage system of Claim 16, wherein:
 the first interface protocol is a Fibre Channel interface protocol.
20. The storage system of Claim 16, wherein:
 each of said plurality of storage devices includes a plurality of registers and a command
 register; and
 said interface adapter is configured to receive a first plurality of frames corresponding to
 an I/O transaction generated by the host device, wherein said interface adapter is
 configured to convert said first plurality of frames into a plurality of register
 inputs and a command input corresponding to said I/O transaction, wherein said
 interface adapter is configured to cause said plurality of register inputs to be
 loaded into the plurality of registers on one of said plurality of storage devices,
 and wherein said interface adapter is configured to cause said command input to
 be loaded into the command register on said one of said plurality of storage
 devices.
- 25 21. The storage system of claim 20, wherein said first plurality of frames arrive at said
 interface adapter in a serial format, and wherein said interface adapter is configured to
 deserialize said first plurality of frames.
- 30

22. The storage system of claim 20, wherein each of said plurality of storage devices is configured to execute an operation corresponding to said I/O transaction in response to said command input being loaded into said command register of said one of said plurality of storage devices.

5

23. The storage system of claim 20, further comprising:
a storage device interface provided in the interface adapter for communicating with the plurality of storage devices;
wherein said interface adapter includes a first receive buffer and a first transmit buffer
coupled to the host interface, and said interface adapter further includes a second
receive buffer and a second transmit buffer coupled to the storage device
interface, wherein said first plurality of frames is received in said first receive
buffer, and wherein said plurality of register inputs is received in said second
transmit buffer prior to being loaded into said plurality of registers.

10

24. The storage system of claim 20, wherein:
one of said plurality of storage devices is configured to generate a plurality of register
outputs corresponding to said I/O transaction; and
said interface adapter is configured to receive said plurality of register outputs from said
one of said plurality of storage devices, convert said plurality of register outputs
to a second plurality of frames, and convey said second plurality of frames to said
host interface.

15

20

25. The storage system of Claim 16, wherein:
each of said plurality of storage devices includes a plurality of registers and a command
register; and
said interface adapter includes a state machine configured to receive a plurality of frames
corresponding to an I/O transaction from said host interface, wherein said state
machine is configured to convert said plurality of frames into a plurality of
register inputs and a command input corresponding to said I/O transaction,
wherein said state machine is configured to cause said plurality of register inputs

25

30

to be loaded into the plurality of registers on one of the plurality of storage devices, and wherein said state machine is configured to cause said command input to be loaded into the command register on said one of the plurality of storage devices.

5

26. The storage system of Claim 25, wherein said plurality of frames arrive at said state machine in a serial format, and wherein said state machine is configured to deserialize said plurality of frames.

10 27. The storage system of Claim 25, further comprising:
 a storage device interface provided between the interface adapter and the plurality of storage devices;
 a first receive buffer coupled to said host interface;
 a first transmit buffer coupled to said host interface;
 a second receive buffer coupled to said storage device interface; and
 a second transmit buffer coupled to said storage device interface;
 wherein said plurality of frames is received in said first receive buffer, and said plurality of register inputs is received in said second transmit buffer prior to being loaded into said plurality of registers.

20 28. An apparatus comprising:
 a host device coupled to a first connection device;
 a plurality of bus devices coupled to a second connection device;
 an interface adapter, wherein said interface adapter includes a first interface coupled to
 25 said first connection device and a second interface coupled to said second connection device;
 wherein said interface adapter is configured to receive a first plurality of frames corresponding to an input/output (I/O) transaction generated by said host device, wherein interface adapter is configured to convert said first plurality of frames into a plurality of register inputs and a command input corresponding to said I/O
 30 transaction, wherein said interface adapter is configured to cause said plurality of

register inputs to be loaded into a plurality of registers on each of said plurality of bus devices, and wherein said interface adapter is configured to cause said command input to be loaded into a command register on each of said plurality of bus devices.

5

29. An apparatus comprising:

a first interface;

a second interface; and

a state machine coupled to said first interface and said second interface;

10 wherein said state machine is configured to receive a plurality of frames corresponding to a input/output (I/O) transaction from said first interface, wherein said state machine is configured to convert said plurality of frames into a plurality of register inputs and a command input corresponding to said I/O transaction, wherein said state machine is configured to cause said plurality of register inputs to be loaded into a plurality of registers on a device coupled to said second interface, and wherein said state machine is configured to cause said command input to be loaded into a command register on said device.

30. A computer system comprising:

an array controller coupled to a first connection device;

at least one server computer coupled to said array controller;

a plurality of bus devices coupled to a second connection device; and

an interface adapter coupled to said first connection device and said second connection device;

25 wherein said at least one server computer is configured to generate an input/output (I/O) transaction, wherein said array controller is configured to receive said I/O transaction and generate a first plurality of frames corresponding to said input/output (I/O) transaction, wherein said interface adapter is configured to receive said first plurality of frames, wherein interface adapter is configured to convert said first plurality of frames into a plurality of register inputs and a command input corresponding to said I/O transaction, wherein said interface

30

adapter is configured to cause said plurality of register inputs to be loaded into a plurality of registers on each of said plurality of bus devices, and wherein said interface adapter is configured to cause said command input to be loaded into a command register on each of said plurality of bus devices.

500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000